



ST-AC Series Powder Coated, Manual Timer, Two Taps, Landscape, Low Voltage Series Landscape low voltage lighting transformer specifically designed for LED landscape fixtures. The transformer has two output options 12V and 15V for either a short and long distance circuits to compensate wire drop voltage. High grade core and copper winding provide excellent load regulation and efficiency. Built in manual 24h timer and photocell provide full control and energy savings. Secondary push to reset circuit breaker provide short circuit and overload protection. Removable slide door. Suitable for Wet Location, ETL Listed to UL STD 1838, CSA STD C22.2 250.0 and 250.7

Wattage: 75-600W

Output Voltage: 12V, 15V

Input Voltage: 120V 60Hz

All: Built in manual timer and photocell, secondary circuit breaker, line cord, compact, economy solution.

Lanscape Transformers ST-AC Series-Slide Series Specification

| Model No. | Wattage | Input Voltage | Output Voltage | Terminal Block | Secondary Breaker | Num. of circuits |
|-----------|---------|---------------|----------------|----------------|-------------------|------------------|
| ST75WL | 75W | 120V 60Hz | 12VAC or 15VAC | √ | √ | single |
| ST100WL | 100W | 120V 60Hz | 12VAC or 15VAC | √ | √ | single |
| ST150WL | 150W | 120V 60Hz | 12VAC or 15VAC | √ | √ | single |
| ST200WL | 200W | 120V 60Hz | 12VAC or 15VAC | √ | √ | single |
| STS300WL | 300W | 120V 60Hz | 12VAC or 15VAC | √ | √ | single |
| ST600WL | 600W | 120V 60Hz | 12VAC or 15VAC | √ | √ | single |